



Construction:

- Handling arm 1
- 2 Circlips
- 3 Fixation pin
- Distance piece 4
- 5 Inner bush
- 6 Tension spring
- 7 Spring washer
- 8 Gasket
- 9 Glass disc
- O-Ring 10
- 11 Fixation bush
- Wiper-blade holder 12
- O-Rings for holder 13
- Wiper-blade 14





Wipers for sightglass discs Series W / WD / WDT / WR / WDR

Application:

Wipers of the series W / WD / WDT / WR / WDR are built into sightglasses similar to DIN 28120 or DIN 11851 to prevent cristallisation of the media inside the vessel onto the inner side of the glass disc or to hold the sightglass free of dust and / or dirt.

The wipers are mounted into glass discs with a centric hole of a diameter of 10,5 mm.

Materials (standard)

Wiper-blade:	PTFE, silicone rubber, silicone rubber FDA
Mechanical parts:	Stainless steel
Glass discs:	Sodium silicate similar to DIN 8902 or
	Borosilicate similar to DIN 7080
	Macrolon on request (only for pressureless operation at ambient

equest (only for pressureless operation at amble temperature)

Operating conditions:

- 1. Maximum pressure inside the vessel: 2 to 6 bar, depending of the glass diameter (see table overleaf). For higher pressures, please consult us.
- 2. Vacuum: Values on request
- 3. Maximum temperatures: 180 °C with wiper-blade of silicone rubber 200 °C with wiper-blade of PTFE

Possible combinations (only for wipers fo the series W / WD): Sightglasses to or similar to DIN 28120:

Series / DN	50	80	100	125	150	200
HL	X					
MVLR	\odot					
BKVLR / BKVLR LED / KVL	\odot	\odot	\odot			
fibroLUX / fibroLUX E	X					
KVLR	X	\odot	\odot			
KLR	X	Х	\odot	\odot		
EdelEx (LED) / (F)(L)KEL / (F)HEL (LED) / KL / FHL	X	Х	\odot	\odot	\odot	
Sightglasses similar to DIN 11851:						

Series / DN	50	65	80	100	125	150
HLM / HLMR	X					
MVLR	X	Х	\odot			
BKVLR / BKVLR LED / KVL	X	Х	\odot	\odot	\odot	
fibroLUX / fibroLUX E	X	Х	Х			
KVLR	X	Х	Х	\odot	\odot	
KLR / EdelEx (LED)	X	Х	Х	X	\odot	\odot
(F)(L)KEL / (F)HEL (LED) / KL / FHL	X	Х	Х	X	Х	۲

X = Can not be combined • = May be combined • = May be combined without restrictions

Type designations:

Version with one wiper-blade, manipulation by handling arm and ratch:				
Version with double wiper-blade, manipulation by handling arm and ratch:	Type WD			
Version with double wiper-blade, manipulation by T handle:	Type WDT			
Version with one wiper-blade, manipulation by knob:	Type WR			
Version with double wiper-blade, manipulation by knob:	Type WDR			

Additional remarks:


- The glass discs with centric hole and the wipers may be ordered separately. In case of complete orders, they leave our works as premounted units.
- The wipers for the screwed sightglasses similar to DIN 11851 of the DN 40 are only available with the knob version.
- The wipers of the type WDT can only be combined with few series of light fittings. Please consult us.

MAX MÜLLER AG

Your reliable and efficient partner in sightglasses. Perfect, thoroughly engineered solutions from one hand! Always an interesting, technically advanced idea ahead!




Dimensions Supplementary informations



The following table is valid for $\mathsf{VETROLUX}^{\texttt{®}}$ sightglasses to or similar to DIN 28120.

DN	Free view	Length of	0	С	Maximum
		wiper-blade	(diameter x thickness)		pressure
	(mm)	(mm)	(mm)		(bar)
50	80	26	99 x 15	38	6
80	100	36	125 x 15	48	4,5
100	125	48	150 x 15	60	3
125	150	61	175 x 15	73	3
150	175	73	200 x 15	85	2
200	225	98	250 x 15	110	2

Type W



Special dimensions on demand. (Up to DN 400)

The following table is valid for screwed sightglasses $\mathsf{VETROLUX}^{\texttt{B}}$ similar to DIN 11851.

DN	Free view (mm)	Length of wiper-blade (mm)	Dimensions of the glass disc (diameter x thickness) (mm)	С	Maximum pressure (bar)
	(1111)	(1111)	(11111)		(641)
40	40	11	51 x 7,5	18	3
65	65	18	84 x 10	30	4
80	80	26	99 x 15	38	6
100	100	36	114 x 15	48	5
125	125	48	147 x 15	60	3
150	150	61	175 x 15	73	3

Special dimensions on demand.

Do you wish for more information about our wide range of light fittings for use in hazardous or safe areas, our camera systems for hazardous areas, about our range of circular sightglasses to or similar to DIN 28120/28121, screwed sight-glasses similar to DIN 11851, rectangular or D-ended sightglasses, pipeline flow indicators, sideways operated wipers, hinged sightglasses, spraying devices or our complete sight and lightglass units VETROLUX®? Are you interested in other types, special versions or different protection degrees? If yes, please contact us, our branch office or our local agents – it is our business! You will find the necessary indications about our sales network on the Internet.

All dimensions in mm.

Subject to changes without preliminary notice.



